

# MANGUERA

LED e incandescente

	Gama	Conexiones máximas	W	V	Int. Ext.	*	Q	Q	Q	Referencia	
	led Pro	50 - x2		3	230			2	36	1800	IBR13HWL
	led Pro	50 - x2		2,6	230			2	36	1800	IBR13WL
	led Pro	50 - x2		2,6	230			2	36	1800	IBR13MWL
	mb Pro	50 - x2		16,6	230			2	36	1800	IBR13W
	led Pro	50 - x2		2,6	230			2	36	1800	IBR13GWL
	mb Pro	50 - x2		16,6	230			2	36	1800	IBR13Y
	led Pro	50 - x2		1,7	230			2	36	1800	IBR13YL
	led Pro	50 - x2		1,7	230			2	36	1800	IBR13RL
	mb Pro	50 - x2		16,6	230			2	36	1800	IBR13R
	led Pro	50 - x2		1,7	230			2	36	1800	IBR13GL
	mb Pro	50 - x2		16,6	230			2	36	1800	IBR13G
	led Pro	50 - x2		2,6	230			2	36	1800	IBR13BL
	mb Pro	50 - x2		16,6	230			2	36	1800	IBR13B



Color de bombillas   
 Horizontal (m)   
 Cable blanco   
 Interior y exterior   
 (W) Watts   
 \* Intermittencia   
 Lámparas por línea  
 Led / MicroBombilla   
 Vertical (m)   
 Cable transparente   
 Interior   
 (V) Voltios   
 N° líneas   
 Lámparas totales



Manguera de luz LED en forma de zig zag sobre árboles de una avenida (IBR13WWL)



Manguera de luz LED perfilando iglesia renacentista (IBR13WL)